

Meterman LCR Meter

Model LCR55 has 28 control positions to measure a wide range of component values. Measure Inductance with seven ranges from 200 μ H to 200H. Achieve a resolution of 0.1 μ H in the 200 μ H range. The Capacitance feature has nine ranges from 200 pF to 20 mF. It provides resolution of 0.1 pF in the 200 pF range. Measure resistance with seven ranges from 20 Ω to 20 M Ω , its extremely fine resolution is 0.01 Ω in the 20 Ω range. Meter allows you to zero out stray capacitance or resistance with a front panel control. LCR55 also tests diodes, including microwave diodes and has test socket for transistor testing.

Model LCR55 has a large 0.7" LCD display and is shipped with one pair of test leads and alligator clips.

Ordering Information

Order #	Mfg #	Description	Price
MPLCR55	LCR55	LCR Meter, Hand Held	
MPH30Y	H30Y	Protective Holster	
Transcat Accredited Calibration with Data			CALL
Transcat Accredited Calibration without Data			CALL



LCR55

B & K Capacitance Meter

- Ten Ranges
- High Resolution

Specifications

Ranges:	10 automatically selected from 199.9 pF to 199.9 mF
Accuracy:	$\pm 0.2\%$ of rdg, +0.5 pF + 1 d to 19.99 μ F; $\pm 1.0\%$ of rdg, + 1 d > 20 μ F
Resolution:	0.1 pF, lowest range
Display:	31/2-digit LCD
Power Supply:	Four C batteries, alkaline
Size/Weight:	4.4 x 6.4 x 2.4" HWD/1.6 lbs

Ordering Information

Order #	Mfg #	Description	Price
MP7494E	830A	Autorange Digital Capacitance Meter	
MP7495E	BC-28	AC Adapter/Charger	
Transcat Accredited Calibration with Data			CALL
Transcat Accredited Calibration without Data			CALL

Each Unit Includes:

Tilt-stand (804-025-9-001), spare fuse (1A, 250V), and instructions.

NOTE: The 9V alkaline batteries are not included.



830A

B & K LCR Meter

- Measures Capacitance, Resistance, and Inductance
- Dual LCD Displays for Measured Value and Q or DF

Specifications

"C" Range/Accuracy:	10 mF to 1000 pf/ $\pm 0.7\%$ + 3 counts, typical
"R" Range/Accuracy:	10 M Ω to 10 Ω / $\pm 0.5\%$ + 3 counts, typical
"L" Range/Accuracy:	10 H to 1 mH/ $\pm 0.7\%$, typical
Size/Weight:	1.5 x 3.5 x 7.6" HWD/13.8 ozs

Ordering Information

Order #	Mfg #	Description	Price
MP4934E	878	LCR Meter/Dual Display	
Transcat Accredited Calibration with Data			CALL
Transcat Accredited Calibration without Data			CALL

Each Unit Includes: Test leads (3468E), AC adapter, and instructions.

NOTE: The 9V alkaline batteries are not included.



878