

Bacharach Refrigerant and Combustible Leak Detectors

- Dual Unit Model-Two Functions
- Sequential Flashing Probe Tip, Dual LED Displays and Loud Tick Rate Indicate Relative Concentration Level
- Detect All Halogens and Combustible Hydrocarbons
- Swappable Sensor Tips
- Hydrophobic Filter Prevents Moisture Contamination
- Automatic Sensitivity Adjustment
- Sensors are Industry's Most Responsive 0.2 Seconds
- Adjustable Probe Length 3 to 20"
- One Year Warranty Including Sensors

Specifications

Refrigerants Detected	All CFC, HCFC, and HFC Including R-12, R-22, R-123, R-134a and Blends R-404A, R-408A, R-409A and R-410A (Any refrigerant containing Chlorine, Fluorine or Bromine)
Combustible Gases Detected	All Combustible Gases and Vapors
Alarm Sensitivity	Refrigerant: 0.25 oz/yr of R-134a (hardest to detect refrigerant) Combustibles: Minimum 50 ppm (methane)
Power	Four (4) AA Alkaline Batteries (4-5 Hours Typical Operation)
Size (HWD)/Weight	1.75x9.62x2.25" (4.44x 4.435.72 cm)/0.86 Lbs. (0.39 kg)
Agency Approvals	Refrigerant: UL Listed in Accordance with SAE J1627 Combustibles: MET Lab Certified to UL 913 Intrinsically Safe for Use in Class I, Div I, Group D

Each Basic Kit Includes: Detector unit and sensor(s), color coded tip(s), 4 AA batteries, 5 filters, soft carrying case and instructions.

Each Deluxe Kit Also Includes: 2 additional AA batteries, protective rubber boot, MagLite®, and a hard carrying case.



19-8042

Ordering Information

Order #	Description	Price
MP19-8042	Dual Refrigerant/Combustible Informant 2 Detector Kit	
MP19-8045	DELUXE Dual Refrigerant/Combustible Informant 2 Detector Kit	
MP19-8040	Refrigerant ONLY Informant 2 Detector Kit	
MP19-8043	DELUXE Refrigerant ONLY Informant 2 Detector Kit	
MP19-8041	Combustible Gas ONLY Informant 2 Detector Kit	
MP19-8044	DELUXE Combustible Gas ONLY Informant 2 Detector Kit	
MP19-8047	Combustible Gas Upgrade Kit (Upgrades Refrigerant to Dual)	
MP19-8046	Refrigerant Upgrade Kit (Upgrades Combustible Gas to Dual)	
MP19-0499	Replacement Combustible Sensor	
MP19-0510	Replacement Refrigerant Sensor	
MP19-0509	Replacement Filters (Pk/5)	
MP19-0497	Protective Rubber Boot	

NEW Bacharach Refrigerant Leak Detector

- Quickly and Accurately Mark any Leak Spot
- Detects all CFC, HFC, and HCFC Refrigerants
- Patented Heated Diode Sensor Technology Allows Instant Response
- Instantaneous Response Time
- Innovative Sensor Replacement Design
- Long-life, DC Brushless Fan
- High and Low-Sensitivity Modes
- Automatic Zero and Background Compensation
- Audible & Visual Leak Indication
- No User Calibration Required

Specifications

Sensing Elements	
Type:	Patented Heated Diode, Plug-in
Life Expectancy:	Typically 150 hours or 1 year of normal use
Refrigerants	All CFC, HCFC and HFC refrigerants, including R-12, R-22, R-123, R-134a and blends R-404A, R-408A, R-409A, and R-410A
Alarm Sensitivity of R-134a	(Hardest to detect refrigerant) 0.5 oz / year (14g / year) per SAE J1627 0.1 oz / year (3g / year) when probe is held over leak source for at least 5 secs
Alarm Types	Variable-intensity audible and visual alarms
Power Source	Two 'D' Alkaline Batteries (15 hours minimum)
Warm-up Time	10 seconds
Response Time	Instantaneous
Probe	14" (356mm) flexible
Size (WLH) (Excluding Probe)	2.12 x 9.5 x 2.4" (53.8 x 241.3 x 61.0 mm)
Weight	1.16 lb. (0.53 kg) w/ batteries
Agency Approvals	UL certified to SAE J1627 CE Mark
Warranty	One year



19-8106

Each Unit Includes: instruction manual, 2 Alkaline 'D' Batteries and hard carrying case

Ordering Information

Order #	Description	Price
MP19-8106	Tru-Pointe Refrigerant Leak Detector	