

Branson Ultrasonic Cleaners

Are you scrubbing, soaking, or steam cleaning? Put away your brushes, soak solutions and steamers—ultrasonic is the way to clean

- Remove Grease, Heavy Oils/Wax, Scale, Resins, Oxides, and Much More
- Deep Cleaning Action—Even in Blind Holes and Every Wetted Internal Surface
- Mechanical or Digital Timers and Controls
- Thermostatically-Controlled Solution Temperature

Some Industrial Uses (Remove dirt, grease, wax, or oils) switches, relays and motors, gears, fittings/parts/connections-metal or plastic precision bearings

Some Electronic Uses (Remove flux and contaminates) PC boards/SMDs, ceramic substrates, capacitors, quartz crystals

Ultrasonic baths create millions of highly agitated microscopic bubbles that do your cleaning for you. These units feature heavy-duty 40 kHz ultrasonic transducers usually found only on larger industrial equipment. Their sweep frequency assures excellent cleaning throughout the bath.

Used with a cleaning solution, they blast dirt from all of your equipment surfaces and cavities alike.



▲ Branson Cleaners

This family of ultrasonic cleaners is available in five tank sizes to meet your job requirements. Each model has a mechanical or digital timer, and several models also provide heating of the bath solution. Digital models offer the maximum control of time (up to 99 minutes) and bath temperature. All units can be used with any of the biodegradable cleaning solutions listed.

Each Unit Includes: Tank cover.

Specifications

	15023UC	5024UC	15027UC	5025UC	5026UC
Tank Size (in "LWD):	6 x 5.5 x 4	9.5 x 5.5 x 4	11.5 x 6 x 6	11.5 x 9.5 x 6	9.5 x 11 x 6
Tank Capacity (gal/l):	0.5/1.9	0.75/2.8	1.5/5.7	2.5/9.5	5.5/20.8
Temp. Range:	Mechanical: 69°C (156°F) Digital: From 20 to 69°C (68 to 156°F)				
Cleaning Time:	Mechanical: 0–60 minutes with continuous hold; Digital: 0–99 minutes				
Power Supply:	115 VAC (Optional 230 VAC)				
Size (in "LWD):	10 x 12 x 11.5"	13.5 x 12 x 11.5"	16 x 12 x 14.5"	16.5 x 15.5 x 14.5"	24 x 18 x 14.5"
Weight (lb/kg):	7/3.2	10/4.5	12/5.4	15/6.8	23/10.4

Ordering Information

Order #	Tank Size	-1 Bath	-2 Bath/Heater	-3 Digital
MP15023UC-□	0.5 Gal			
MP5024UC-□	0.75 Gal			
MP15027UC-□	1.5 Gal			
MP5025UC-□	2.5 Gal			
MP5026UC-□	5.5 Gal			
MP5027UC-4	Electronics Cleaning Solution (CS/4 Gallon)			
MP5028UC-12	General Purpose Solution (CS/12 Quart)			
MP5029UC-12	Industrial Strength Cleaning Solution (CS/12 Quart)			
MP15028UC-4	Metal Cleaner Al/Cu/Brass/Steel Substrates (CS/4 Gallon)			
MP15029UC-4	Metal Cleaner Fe/Al/Cu/SS/Ti, and Alloys (CS/4 Gallon)			

Optional Insert T rays

For Model #	Order # Solidray	Price	Order # Perforatedray	Price
MP15023UC	MP15032UC		MP15033UC	
MP5024UC	MP5035UC		MP5036UC	
MP15027UC	MP15044UC		MP15045UC	
MP5025UC	MP5038UC		MP5039UC	
MP5026UC	MP5041UC		MP5042UC	

Insert the ordering codes in the box to select the model suited for your application:

- 1 (Bath with timer only)
- 2 (Bath with mechanical timer and fixed temperature heater with continuous hold button)
- 3 (Bath with settable digital timer and temperature range)

NOTE:

Cleaning solutions will be drop shipped

NOTE:

For 230V models add -230 to the end of the catalog number.